



COMMERCIAL DIVISION

The Professional Range

PRO 100 & 200



AVAILABLE WITH
METAL FACIA



PUMP



HOUR METER



2 SPEED FAN



FILTER

FLOOD & RESTORATION • ROOF LEAKS • BASEMENTS / CELLARS
LAUNDRIES • VEHICLE STORAGE • HOTELS / GUEST HOUSES
SECOND HOMES • LABORATORIES • OFFICES

Ebac's PROFESSIONAL RANGE

When Ebac launch a product, you can be sure it's aimed at specific customer needs. The Pro100 and Pro200 are no exception, designed to meet the Restoration Industries specifications, coupled with the renowned Ebac ruggedness and high quality standards these models form the base of the new generation of high performance dehumidifiers

SAVE TIME AND MONEY

No more worries of forgetting to empty buckets, due to customer demands, the Professional range is supplied complete with an integral, high capacity condensate pump. The 10-foot maximum pump height will ensure no installation is too difficult. Install, connect to a permanent drain and forget until the job is complete. With the aid of a purge facility, all residue water can be drained from the pump integral tank prior to moving the machine therefore eliminating the chances of spillage.

LOW TEMPERATURE OPERATION

A "Hot Gas" defrost system, ensures quick and efficient clearing of ice from the coil, allowing a minimum operating temperature of 3°C.

The Pro200 is also equipped with a microprocessor, intelligent temperature defrost control, this unique features ensure the highest possible performance across broader operating temperatures.

DESIGNED AND BUILT TO LAST

The integral tubular welded chassis, ensures the equipment will withstand the harsh operating environment. While the tough Stoved Epoxy powder finish will ensure the product maintains a high visual appearance. The large rear wheels of the Pro200 allow easy transport up/down stairs and the castors with rubber tyres reduces the risk of damage to flooring.

The collapsible handle of the Pro200 allows it to be transported in small vans and estate / hatchback cars, and easily manoeuvred during installation

MANAGEMENT FEATURES

How many times do you install equipment, only to find the customer switches the unit off immediately you leave the premises. The internal Hour Meter will provide a visual indication of the drying time. However the twin speed fans gives the customer the option to reduce noise during evening & night time operation

ATTENTION TO DETAIL

Sometimes the less expensive features are overlooked. Both units are supplied complete with cable and hose ties. Not only will this reduce possible damage while the units are transported, but also provides easy installation when positioning onsite.

APPLICATIONS

- Flood & Restoration
- Roof Leaks
- Basements / Cellars
- Laundries
- Vehicle storage
- Hotels / Guest Houses
- Second Homes
- Laboratories
- Offices



Specification	Pro 100	Pro 200	
ABS Grille Version	10291PP-GB	10292PP-GB	
Metal Grille Version	10291MP-GB	10292MP-GB	
Height	670	800	mm
Width	355	510	mm
Depth	380	40	mm
Weight	22	40	kg
Voltage	230	230	V
Power	325	500	W
Current	2.4	2.5	A
Supply Fuse Rating	13	13	A
Airflow	150	328	m3/hr
Pump-Max Extraction	3	3	m
Typical Water Extraction	15	20	Lts/day

Features		
2 Speed Fan	Y	Y
Hot Gas Defrost	Y	Y
Pump & Purge Switch	Y	Y
Hour Meter	Y	Y
Carrying Handles	Y	Y
Washable Filter	Y	Y
Front Castor Mounted	Y	Y
ABS or Metal Grille Ver	Y	Y
Large Rear Wheels	N/A	Y
Collapsible Handle	N/A	Y
Cable & Hose Tidy	Y	Y
Refrigerant	R134a	R407C
Fitted Plug	Y	Y
Robust Tubular Chassis	Y	Y
Stoved Epoxy Finish	Y	Y